

BS 2/TE Belt Section




- Ready for operation with drive for transverse conveyor into a dead end
- Additional toothed gear to drive one HQ 2/O lift transverse unit



Assembly instructions

- Reversible operation possible
- Conveyor medium: Toothed belt (suitable for use in an EPA)
- Can be combined with WT 2/E, WT 2, WT 2/F, WT 2/H and WT 2/F-H

Product description



Energy efficiency – Rexroth 4EE

Technical data

No.			3842999723
Max. section load in accumulation operation		kg	60
ESD			yes
Length	l	mm	240 ... 6000

-


Transport and nominal speed vN

-

Compressed air consumption of TS 2plus units


Dimensions

BS 2/TE Belt Section



00116828

Ordering codes



Order Parameter

No.		3842999723
b (mm)	Track width in the direction of transport	160; 240; 320; 400; 480; 640; 800
l (mm)	Length	240 ... 6000
v_N (m/min) ¹⁾	Nominal speed	0; 6; 9; 12; 15; 18
U, f (V, Hz)	Voltage, frequency	see motor data
AT	Motor connection S: cable/plug K: terminal box	S; K
MA ²⁾	Motor mounting R: right L: left M: center	R; L; M
UB	Connection belt UB = 1 UB = 2	1; 2

1) $v_N = 0$: without motor or gear

2) MA = M from $b_Q \geq 320$ mm and above

	No.
BS 2/TE Belt Section	3842999723