

Strut profile 40x45°



Product description

[Quick & Easy profile finishes](#)

[Introduction to strut profiles](#)

Technical data

[Quick & Easy profile finishes](#)

Dimensions


Strut profile 40x45°

40x45°

$A = 6,8 \text{ cm}^2$
 $I_x = 9,9 \text{ cm}^4$
 $I_y = 16,6 \text{ cm}^4$
 $W_x = 5,0 \text{ cm}^3$
 $W_y = 8,3 \text{ cm}^3$
 $I_t = 4,2 \text{ cm}^4$
 $W_t = 3,7 \text{ cm}^3$
 $m = 1,8 \text{ kg/m}$



19206



Ordering codes

The following cover caps can be used:

Cover cap 40x45°, signal gray (1x)

Cover cap 40x45°, black (1x)

	L			ESD	No.
	mm				
Strut profile 40x45°	50 ... 6070		1		3842993197
Strut profile 40x45° 12xL=6070mm	6070	12			3842529373
Strut profile 40x45° Q&E	50 ... 6070		1		3842993726
Cover cap 40x45°, black ESD			20		3842551017
Cover cap 40x45°, signal gray			20		3842551016
Strut profile 40x45°	6070		1		3842529374

Standard profile finishing Lmax = 6000 mm (note minimum length)		M12
---	--	-----